

3m x55i projector manual



File Name: 3m x55i projector manual.pdf

Size: 2163 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 29 May 2019, 20:42 PM

Rating: 4.6/5 from 616 votes.

Status: AVAILABLE

Last checked: 11 Minutes ago!

In order to read or download 3m x55i projector manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with 3m x55i projector manual . To get started finding 3m x55i projector manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

3m x55i projector manual

About this manual Various symbols are used in this manual. The meanings of these symbols are described below. WARNING This symbol indicates information that, if ignored, could possibly result in personal injury or even death due to incorrect handling. CAUTION This symbol indicates information that, if ignored, could possibly result in personal injury or physical damage due to incorrect handling. Please refer to the pages written following this symbol. Part names Projector Control buttons Cursor buttons Arrangement. Refer to the illustrations and tables below to determine the screen size. Using the Security Bar Examples of connection with a computer Connecting power supply Using the remote control Adjusting the volume Selecting an input signal continued Using the automatic adjustment feature Using the menu function VIDEO RGB SEARCH EASY Menu continued PICTURE Menu continued With the IMAGE menu, items shown in the table below can. With the INPUT menu, the items shown in the table below. With the SETUP menu, the items shown in the table below. SCREEN Menu continued With the OPTION menu, the items shown in the table below. Maintenance Lamp Air lter Other care Regarding the indicator lamps. Lighting and ashing of the POWER indicator, the LAMP indicator, . Regarding the indicator lamps continued Phenomena that may be easy to be mistaken for machine defects Phenomena that may be easy to be mistaken for machine defects continued Specifications continued Page 53 Page 54 Intended Use. Before operating this machine, please read this entire manual thoroughly. The 3MTM Multimedia Projectors are designed, built, and. We have 5 3M Multimedia Projector X55i manuals available for free PDF download Operators Manual, Quick Start Manual, Specification Sheet. Do not look into the lens of projector. Also do not peep at the inside of projector through a hole. Operating Selecting an aspect ratio 1. Press the ASPECT button on the remote control. <http://www.lichtengeluid.eu/images/uploaded/comcast-motorola-dct3416-manual.xml>

- **3m x55i projector manual, 3m x55 projector manual, 3m x55i projector manual, 3m x55i projector manual download, 3m x55i projector manual free, 3m x55i projector manual instructions, 3m x55i projector manual 2017, 3m x55i projector manual 2016, 3m x55i projector manual online, 3m x55i projector manual software, 3m x55i projector manual downloads.**

The "FREEZE" indication will appear on the screen, and the projector will enter the FREEZE mode. See the ASPECT item in the IMAGE menu 30 . KEYSTONE Using the buttons corrects the keystone distortion. The startup screen is a screen displayed when no signal or an unsuitable signal is detected. TURN ON TURN OFF This function works with INPUT, RGB, and VIDEO buttons. The signal cables are not correctly connected. The 3M TM Multimedia Projectors are designed, built, and tested for use indoors, using 3M lamps, 3M ceiling mount hardware, and nominal local voltages. Please check your inbox, and if you can't find it, check your spam folder to make sure it didnt end up there. Please also check your spam folder. After reading them, store them in a safe place for future reference. The meanings of these symbols are described below. It requires just a little space for installation and gets a large image from short distance. The image can be still kept as bright and clean enough for use in bright rooms. It is perfect for use in low luminance rooms where low noise is more important than brightness. It can be easily connected to many signal sources like PC, DVD and so on. The rich connectivity provides you more options to make your presentation impressive. Contact immediately your dealer if anything is missing. For moving the projector, be sure to use the original packing materials. Use special caution for the lens part. When this switch is not pushed in, RGB IN2 is selected. In such a case, please push the Restart switch by using a cocktail stick or

similar, and before turning on again, make the projector cool down at least 10 minutes without operating. Only push the Restart switch in these exceptional instances. Put nothing on the projector. This projector To prevent damaging the projector and injuring yourself, always hold the projector whenever using the elevator buttons to adjust the elevator feet. Also do not incline it backward or forward exceeding 9 degrees. <http://fuerst-architects.com/uploads/comcast-motorola-dct2500-manual.xml>

Exceeding these range could cause malfunction, and could shorten the lifetime of the consumables. The adjustment range of the elevator feet is 0 to 9 degrees. Dropping or knocking over the projector may cause damage or injury. It is intended to be used as an extra theft prevention measure. Some cables have to be used with core set. A too long cable may cause a certain picture degradation. Please consult with your dealer for details. For cables that have a core only at one end, connect the core to the projector. For details on how this is done, please refer to the instruction manual of the corresponding laptop computer. Use of some of these modes will not be possible with this projector. Then the resolution will go back to the original. It might be recommended to use other CRT or LCD monitors to change the resolution. PlugandPlay can be achieved by connecting this projector to a computer is VESA DDC display data channel compatible. PlugandPlay may not work properly if any other type of connection is attempted. To change the settings, refer to the AUDIO item in the SETUP menu. 34 To change the settings, refer to the AUDIO item in the SETUP menu. 34 If it is damaged, contact your dealer to newly get correct one. Never attempt to defeat the ground connection of the threepronged plug. Do not mix a new battery with used one. If the liquid adheres to your body or clothes, rinse well with water immediately. It may result in malfunction. Adjust the direction of the projector to keep the light from directly hitting the projector's remote sensor. Also do not peep at the inside of projector through a hole. Please power on the projector prior to the connected devices. Power off the projector later than the connected devices. Then wait several seconds because the buttons may not function for these several seconds. When the power is However, please pay special attention to below two points when you do Neglect could shorten the lifetime of the lamp. Attach the lens cover.

Excellent Picture Quality The LCD technology allows multiple colors to be reproduced all the time resulting in color saturation that does not vary with image brightness; You get bright, vibrant color, all the time Brightness When you are projecting in an area where the lighting can not be controlled, or when you are projecting on to an extremely large screen; With a brightness of 2000 ANSI Lumens you can project in bright rooms Quiet Operation The low fan noise allows the projector to operate for hours without fatigue Keystone Correction Room layout often dictates that images have to be projected at an angle to screen. Let us know YOUR RECENTLY VIEWED ITEMS Browsing History ON Clear History Not responsible for typographical or illustrative errors. We delete comments that violate our policy, which we encourage you to read. Discussion threads can be closed at any time at our discretion. About this manual V arious symbols are used in this manual. WARNING This symbol indicates information that, if ignored, could possibly result in personal injury or even death due to incorrect handling. CA UTION This symbol indicates information that, if ignored, could possibly result in personal injury or physical damage due to incorrect handling. Please refer to the pages written following this symbol. U kunt hieronder aangeven waarom deze vraag ongepast is. Wij controleren de vraag en zonodig wordt deze verwijderd. Emailadressen en volledige namen worden niet als privegegevens beschouwd. Wij vragen u dus ook te reageren op een antwoord. Laat uw emailadres achter op deze site, zodat u op de hoogte blijft. U krijgt dan ook andere vragen en antwoorden te zien. De handleiding is 7,56 mb groot. Als u geen email heeft ontvangen, dan heeft u waarschijnlijk een verkeerd emailadres ingevuld of is uw mailbox te vol. Daarnaast kan het zijn dat uw internetprovider een maximum heeft aan de grootte per email.

<http://www.drupalitalia.org/node/68333>

Omdat hier een handleiding wordt meegestuurd, kan het voorkomen dat de email groter is dan toegestaan bij uw provider. Controleer uw email Vul dan hier uw emailadres in. Please use the box above to search for any other information. For cables that have multiple display screen modes. In this case, you connect devices to. Setting up. Connecting your devices Operating the computer screen Perhaps you believe your AC is cycling too frequently. The usual cause of such shortcycling is th. Thank you for purchasing this projector. Content. Projector features. This projector is used to project various computer signals UHB Ultra High Brightness lamp gives you a higher brightness image on a screen. Part names. Part names Projector. FrontRight side. Control buttons. Remote control. Arrangement. Refer to the illustrations and tables below to determine the screen size and projection distance. Adjusting the projectors elevator. Using the Security Bar. Dropping or knocking over the projector may cause damage or injury. Connecting your devices. Examples of connection with a computer. USB cable. Setting up Connecting power supply. Remote control Putting batteries. If the liquid adheres to your body or clothes, rinse well with water immediately. Using the remote control. Operating. Operating Adjusting the volume Temporarily muting the sound Selecting an input signal continued Each time you press the button, the projector switches its video input port as below. Using the automatic adjustment feature Operating Operating. Operating the computer screen. Multifunctional settings. Multifunctional settings Using the menu function EASY Menu. With the EASY MENU, items shown in the table below can be performed. Then perform it referring to the following table. EASY Menu continued. Performing this item resets all of the items of EASY MENU except FILTER TIME and LANGUAGE. PICTURE Menu. With the PICTURE menu, the items shown in the table below can be performed. PICTURE Menu continued.

<https://jdleducation.com/images/canon-lide-200-user-manual.pdf>

This is not a malfunction. PICTURE Menu continued. Item Description Using the each function. IMAGE Menu. With the IMAGE menu, items shown in the table below can be performed. IMAGE Menu continued. Item Description Using the buttons such a case, please reset the adjustment by pressing the RESET button on the remote control during this operation. Selecting this item performs the automatic adjustment feature. INPUT Menu. With the INPUT menu, the items shown in the table below can be performed. INPUT Menu continued. SETUP Menu. With the SETUP menu, the items shown in the table below can be performed. SCREEN Menu. With the SCREEN menu, the items shown in the table below can be performed. SCREEN Menu continued. Item Description Using the frame for capturing appears. To stop performing, press the RESET or ESC button on the remote control. 2. Using the buttons adjusts the frame position. SCREEN Menu continued. OPTION Menu. With the OPTION menu, the items shown in the table below can be performed. OPTION Menu continued. Item Description Selecting this item displays the SERVICE menu. Maintenance. Maintenance Lamp WARNING Maintenance. Using the lamp for long periods of time could cause the pictures darker or the color tone poor. Other care. Troubleshooting. Related messages. When the units power is on, messages such as those shown below may be displayed. When any such message is displayed on the screen, please follow the instructions described below. Regarding the indicator lamps. Please follow the instructions within the table. Regarding the indicator lamps continued. LAMP TEMP POWER indicator indicator indicator Blinking In Red or Lighting In Red Description. The cooling fan is not operating. Turned off Blinking In Red. Phenomena that may be easy to be mistaken for machine defects. Phenomena that may be easy to be mistaken for working. Sound does not come out. Restore the sound pressing the MUTE or VOLUME button on the remote control.

<http://coconutgroverestaurantnevis.com/images/canon-lens-manuals.pdf>

The volume is adjusted to an extremely low level. The AUDIO setting is not correct. Phenomena Replace the lamp. Pictures appear blurry. The 3MTM Multimedia Projectors are designed, built, and tested for use indoors, using 3M lamps, 3M ceiling mount hardware, and nominal local voltages. The use of other replacement lamps, outdoor operation, or different voltages has The meanings of these

symbols are. Model X55I. This projector is used and is in good working order. You can view sharper and crisp images, as this 3M projector boasts a native resolution of 1024x768 pixels. With a contrast ratio of 4001, this LCD projector renders images and videos in rich colors. Boasting a brightness of 2,000 lumens, this 3M projector lets you clearly view images and videos even in bright light conditions. Supporting multiple connectivity options like composite video, component video, svideo, VGA and DVI, the 3M X55i projector offers flexibility in use. You can easily control the operation of this LCD projector, thanks to its USB mouseemulation support. Product Identifiers Brand 3M MPN X55I Model X55i eBay Product ID ePID 92380269 Product Key Features Aspect Ratio 43 Contrast Ratio 4001 Image Brightness 2000 ANSI Lumens Dimensions Weight 6.4lb. Width 12in. Height 3.3in. Depth 9.8in. Additional Product Features Synchronization Range Horizontal 31.5106kHz Video Input Composite Video, SVideo X 1, Component Video MAX Maximum Resolution 1600x1200 UXGA Speakers Output 1w Light Source Life 2000hr. Verisign. Using the online preview, you can quickly view the contents and go to the page where you will find the solution to your problem with 3M Projector X55I. To start viewing the user manual 3M Projector X55I on full screen, use the button Fullscreen. However, if you do not want to take up too much of your disk space, you can always download it in the future from ManualsBase. The option to print the manual has also been provided, and you can use it by clicking the link above Print the manual.

You do not have to print the entire manual 3M Projector X55I but the selected pages only. paper. If you want to quickly view the content of pages found on the following pages of the manual, you can use them. If you order a projector lamp from our company and you are not satisfied for any reason, you may send the projector lamp back for a full refund or an exchange.If you order a projector lamp from our company and you are not satisfied for any reason, you may send the projector lamp back for a full refund or an exchange.This is in stock and ready to ship. Please try again.You dont have to pay anything extra!!Please try your search again later.You can edit your question or post anyway.It is different from other sellers that only sell the bare lamp or bare bulb. This 3M X55i projector lamp is made in Taiwan and comes with 90 days warranty. All lamps are tested before leaving the manufacturer to ensure the best quality of the lamp.If you are a seller for this product, would you like to suggest updates through seller support Amazon calculates a products star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers and factors that establish reviewer trustworthiness. Includes 2 year warranty. Includes 2 year warranty. Includes 2 year warranty. Includes 2 year warranty. Sign up to our newsletter today. Something went wrong. View cart for details. Sell on eBay Sell Home Theatre Projectors User Agreement, Privacy, Cookies and AdChoice Norton Secured powered by Verisign. Alternatively, choose a bare bulb without housing if you already have experience with replacing bare bulbs and are willing to deal with the more challenging replacement process. If you do not want to compromise on projection quality and reliability, choose an original manufacturer lamp.

doubletroubels.com/wp-content/plugins/formcraft/file-upload/server/content/files/1626be537bc13c---compustar-2wssr-manual.pdf

If you prefer a cheaper option and projection quality and reliability are not your top priority, buy a generic lamp. A suitable compromise is an original bulb inside or diamond lamp. It provides the quality of an original lamp, although for a better price. You can choose from 4 lamp options original, hybrid, diamond or generic.This option is recommended for its maximum reliability and easy replacement process. It is a highly reliable solution. We recommend it as an alternative to original lamps with housing. This is a very reliable solution and is cheaper than the original manufacturer option. We recommend it thank to its reliability and affordable price. It is a cheaper solution recommended for inhome use, where projection quality and reliability are not as crucial. Even though generic lamps are not necessarily of the same quality as original manufacturer lamps, their

price is nevertheless very attractive. You can choose from two options of this bare lamp original or generic. This solution is cheaper than a lamp with housing, although it requires a certain amount of manual skills. This option is recommended for customers who already have some experience with bare bulb replacement. This solution is cheaper than a lamp with housing, although it requires a certain amount of manual skills. This option is recommended for customers who already have some experience with bare bulb replacement. Keep in mind that replacing the bulb in the housing requires manual skills and tools. It is the cheapest option which we recommend for inhome use, where projection quality and reliability are not as crucial. Even though generic bulbs are not necessarily of the same quality as original manufacturer bulbs, their price nevertheless is very attractive. Keep in mind that replacing the bulb in the housing requires manual skills and tools. Even though generic bulbs are not necessarily of the same quality as original manufacturer bulbs, their price nevertheless is very attractive.

Which one should I choose We will help you find the right lamp Please provide us with your contact details below. We will immediately find out for you exactly when the product should be available, so you can place your order accordingly.

<http://www.drupalitalia.org/node/68334>